






















































































|   |   |   |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
|---|---|---|---|---|---|---|---|--|---------------------------------|----------------------------|--|--|--|--|-------------------|---|--|--|--|--|--------|---|---|---|---|--|---------------|---|---|---|---|--------------|---------------|--------------|--|--|--|-------------|
|    | <p><b>Pointer N-1</b></p>   | <table border="1"> <tr> <td>Protection class:</td> <td><b>IP66</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5"><b>t<sub>a</sub> 40 °C</b></td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td colspan="4"><b>II 3GD EEx nA II T4</b></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="5">230 V, 50 Hz</td> </tr> </table>                | Protection class:   | <b>IP66</b>   |    |    |  |  | Admissible ambient temperature: | <b>t<sub>a</sub> 40 °C</b> |  |  |  |  | Insulation class: | I |  |  |  |  | Marks: |    | <b>II 3GD EEx nA II T4</b>  |   |   |  |               |    |    |    |   |              | Power supply: | 230 V, 50 Hz |  |  |  |             |
| Protection class:   | <b>IP66</b>   |    |    |    |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
| Admissible ambient temperature:   | <b>t<sub>a</sub> 40 °C</b>  |   |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
| Insulation class:   | I   |   |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
| Marks:  |    | <b>II 3GD EEx nA II T4</b>  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
|   |    |    |    |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
| Power supply:   | 230 V, 50 Hz  |   |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
|    | <p><b>Vipet N-1</b></p>   | <table border="1"> <tr> <td>Protection class:</td> <td><b>IP66</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5"><b>t<sub>a</sub> 40 °C</b></td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td colspan="4"><b>II 3GD EEx nA II T4 - T5</b></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="5">230 V, 50 Hz</td> </tr> </table>           | Protection class:   | <b>IP66</b>   |    |    |  |  | Admissible ambient temperature: | <b>t<sub>a</sub> 40 °C</b> |  |  |  |  | Insulation class: | I |  |  |  |  | Marks: |    | <b>II 3GD EEx nA II T4 - T5</b>   |   |   |  |               |    |    |    |   |              | Power supply: | 230 V, 50 Hz |  |  |  |             |
| Protection class:   | <b>IP66</b>   |    |    |    |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
| Admissible ambient temperature:   | <b>t<sub>a</sub> 40 °C</b>  |   |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
| Insulation class:   | I   |   |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
| Marks:  |    | <b>II 3GD EEx nA II T4 - T5</b>   |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
|   |    |    |    |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
| Power supply:   | 230 V, 50 Hz  |   |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
|  | <p><b>Rambo</b></p>   | <table border="1"> <tr> <td>Protection class:</td> <td><b>IP42 (IP67)</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5"><b>t<sub>a</sub> 30 °C</b></td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="4"></td> <td>230 V, 50 Hz</td> </tr> <tr> <td></td> <td colspan="4"></td> <td>24 V, 50 Hz</td> </tr> </table>   | Protection class:   | <b>IP42 (IP67)</b>  |  |  |   |  | Admissible ambient temperature: | <b>t<sub>a</sub> 30 °C</b> |  |  |  |  | Insulation class: | I |  |  |  |  | Marks: |  |  |  |  |  | Power supply: |   |   |   |   | 230 V, 50 Hz |               |              |  |  |  | 24 V, 50 Hz |
| Protection class:   | <b>IP42 (IP67)</b>  |    |  |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
| Admissible ambient temperature:   | <b>t<sub>a</sub> 30 °C</b>  |   |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
| Insulation class:   | I   |   |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
| Marks:  |  |    |  |  |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
| Power supply:   |   |   |   |   | 230 V, 50 Hz  |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
|   |   |   |   |   | 24 V, 50 Hz   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
|  | <p><b>Rambo N</b></p>   | <table border="1"> <tr> <td>Protection class:</td> <td><b>IP67</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5"><b>t<sub>a</sub> 40 °C</b></td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td colspan="4"><b>II 3GD; EEx nA II T5</b></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="5">230 V, 50 Hz</td> </tr> </table> | Protection class:   | <b>IP67</b>   |  |  |   |  | Admissible ambient temperature: | <b>t<sub>a</sub> 40 °C</b> |  |  |  |  | Insulation class: | I |  |  |  |  | Marks: |  | <b>II 3GD; EEx nA II T5</b>   |   |   |  |               |  |  |  |  |              | Power supply: | 230 V, 50 Hz |  |  |  |             |
| Protection class:   | <b>IP67</b>   |    |  |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
| Admissible ambient temperature:   | <b>t<sub>a</sub> 40 °C</b>  |   |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
| Insulation class:   | I   |   |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
| Marks:  |  | <b>II 3GD; EEx nA II T5</b>   |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
|   |  |    |  |  |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |
| Power supply:   | 230 V, 50 Hz  |   |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |               |   |   |   |   |              |               |              |  |  |  |             |

|   |   |  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
|---|---|--|---|---|---|---|---|--|---------------------------------|----------------------------|--|--|--|--|-------------------|---|--|--|--|--|--------|---|---|---|---|--|--|---|---|---|---|--|---------------|--------------|--|--|--|--|
|    | <p><b>Aqua N</b></p>  | <table border="1"> <tr> <td>Protection class:</td> <td><b>IP67</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5"><b>t<sub>a</sub> 40 °C</b></td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td colspan="4"><b>II 3GD; EEx nA II T5</b></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="5">230 V, 50 Hz</td> </tr> </table>             | Protection class:   | <b>IP67</b>   |    |    |    |  | Admissible ambient temperature: | <b>t<sub>a</sub> 40 °C</b> |  |  |  |  | Insulation class: | I |  |  |  |  | Marks: |    | <b>II 3GD; EEx nA II T5</b>   |   |   |  |  |    |    |    |    |  | Power supply: | 230 V, 50 Hz |  |  |  |  |
| Protection class:   | <b>IP67</b>   |   |    |    |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
| Admissible ambient temperature:   | <b>t<sub>a</sub> 40 °C</b>  |  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
| Insulation class:   | I   |  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
| Marks:  |    | <b>II 3GD; EEx nA II T5</b>  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
|   |    |   |    |    |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
| Power supply:   | 230 V, 50 Hz  |  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
|    | <p><b>Rambo Ex</b></p>  | <table border="1"> <tr> <td>Protection class:</td> <td><b>IP67</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5"><b>t<sub>a</sub> 40 °C</b></td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td colspan="4"><b>II 2GD; EEx edm IIC T5</b></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="5">230 V, 50 Hz</td> </tr> </table>           | Protection class:   | <b>IP67</b>   |    |    |    |  | Admissible ambient temperature: | <b>t<sub>a</sub> 40 °C</b> |  |  |  |  | Insulation class: | I |  |  |  |  | Marks: |    | <b>II 2GD; EEx edm IIC T5</b>   |   |   |  |  |    |    |    |    |  | Power supply: | 230 V, 50 Hz |  |  |  |  |
| Protection class:   | <b>IP67</b>   |   |    |    |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
| Admissible ambient temperature:   | <b>t<sub>a</sub> 40 °C</b>  |  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
| Insulation class:   | I   |  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
| Marks:  |    | <b>II 2GD; EEx edm IIC T5</b>  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
|   |    |   |    |    |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
| Power supply:   | 230 V, 50 Hz  |  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
|   | <p><b>Aqua Ex</b></p>   | <table border="1"> <tr> <td>Protection class:</td> <td><b>IP67</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5"><b>t<sub>a</sub> 40 °C</b></td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td colspan="4"><b>II 2GD; EEx edm IIC T5</b></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="5">230 V, 50 Hz</td> </tr> </table> | Protection class:   | <b>IP67</b>   |    |    |    |  | Admissible ambient temperature: | <b>t<sub>a</sub> 40 °C</b> |  |  |  |  | Insulation class: | I |  |  |  |  | Marks: |  | <b>II 2GD; EEx edm IIC T5</b>   |   |   |  |  |  |  |  |  |  | Power supply: | 230 V, 50 Hz |  |  |  |  |
| Protection class:   | <b>IP67</b>   |   |    |    |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
| Admissible ambient temperature:   | <b>t<sub>a</sub> 40 °C</b>  |  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
| Insulation class:   | I   |  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
| Marks:  |  | <b>II 2GD; EEx edm IIC T5</b>  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
|   |  |   |  |  |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
| Power supply:   | 230 V, 50 Hz  |  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
|  | <p><b>Pitbul Ex</b></p>   | <table border="1"> <tr> <td>Protection class:</td> <td><b>IP65</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5"><b>t<sub>a</sub> 40 °C</b></td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td colspan="4"><b>II 2GD; EEx edm IIC T5</b></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="5">230 V, 50 Hz</td> </tr> </table>  | Protection class:   | <b>IP65</b>   |  |  |  |  | Admissible ambient temperature: | <b>t<sub>a</sub> 40 °C</b> |  |  |  |  | Insulation class: | I |  |  |  |  | Marks: |  | <b>II 2GD; EEx edm IIC T5</b>   |   |   |  |  |  |  |  |   |  | Power supply: | 230 V, 50 Hz |  |  |  |  |
| Protection class:   | <b>IP65</b>   |   |  |  |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
| Admissible ambient temperature:   | <b>t<sub>a</sub> 40 °C</b>  |  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
| Insulation class:   | I   |  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
| Marks:  |  | <b>II 2GD; EEx edm IIC T5</b>  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
|   |  |   |  |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
| Power supply:   | 230 V, 50 Hz  |  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
|  | <p><b>Boxer</b></p>   | <table border="1"> <tr> <td>Protection class:</td> <td><b>IP54</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5"><b>t<sub>a</sub> 25 °C</b></td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td colspan="5"><b>IK 10</b> acc. CSN EN 50102</td> </tr> <tr> <td>Power supply:</td> <td colspan="5">230 V, 50 Hz</td> </tr> </table>  | Protection class:   | <b>IP54</b>   |  |  |   |  | Admissible ambient temperature: | <b>t<sub>a</sub> 25 °C</b> |  |  |  |  | Insulation class: | I |  |  |  |  | Marks: |  |  |  |  |  |  | <b>IK 10</b> acc. CSN EN 50102  |   |   |   |  | Power supply: | 230 V, 50 Hz |  |  |  |  |
| Protection class:   | <b>IP54</b>   |   |  |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
| Admissible ambient temperature:   | <b>t<sub>a</sub> 25 °C</b>  |  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
| Insulation class:   | I   |  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
| Marks:  |  |   |  |  |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
|   | <b>IK 10</b> acc. CSN EN 50102  |  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |
| Power supply:   | 230 V, 50 Hz  |  |   |   |   |   |   |  |                                 |                            |  |  |  |  |                   |   |  |  |  |  |        |   |   |   |   |  |  |   |   |   |   |  |               |              |  |  |  |  |

