




























































































| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|--|---|---|---|---|---|--|---------------------------------|----------------------------|--|--|--|--|-------------------|---|--|--|--|--|--------|---|---|---|---|---|---------------|---|---|---|---|--------------|---------------|--------------|--|--|--|-------------|
|  | <p>Pointer N-1</p> | <table border="1"> <tr> <td>Protection class:</td> <td>IP66</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5">t_a 40 °C</td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td colspan="4">II 3GD EEx nA II T4</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="5">230 V, 50 Hz</td> </tr> </table> | Protection class: | IP66 |  |  |  | | Admissible ambient temperature: | t_a 40 °C | | | | | Insulation class: | I | | | | | Marks: |  | II 3GD EEx nA II T4 | | | | |  |  |  | | | Power supply: | 230 V, 50 Hz | | | | |
| Protection class: | IP66 |  |  |  | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Admissible ambient temperature: | t_a 40 °C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Insulation class: | I | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Marks: |  | II 3GD EEx nA II T4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| |  |  |  | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Power supply: | 230 V, 50 Hz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | <p>Vipet N-1</p> | <table border="1"> <tr> <td>Protection class:</td> <td>IP66</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5">t_a 40 °C</td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td colspan="4">II 3GD EEx nA II T4 - T5</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="5">230 V, 50 Hz</td> </tr> </table> | Protection class: | IP66 |  |  |  | | Admissible ambient temperature: | t_a 40 °C | | | | | Insulation class: | I | | | | | Marks: |  | II 3GD EEx nA II T4 - T5 | | | | |  |  |  | | | Power supply: | 230 V, 50 Hz | | | | |
| Protection class: | IP66 |  |  |  | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Admissible ambient temperature: | t_a 40 °C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Insulation class: | I | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Marks: |  | II 3GD EEx nA II T4 - T5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| |  |  |  | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Power supply: | 230 V, 50 Hz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | <p>Rambo</p> | <table border="1"> <tr> <td>Protection class:</td> <td>IP42 (IP67)</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5">t_a 30 °C</td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="4"></td> <td>230 V, 50 Hz</td> </tr> <tr> <td></td> <td colspan="4"></td> <td>24 V, 50 Hz</td> </tr> </table> | Protection class: | IP42 (IP67) |  |  |  | | Admissible ambient temperature: | t_a 30 °C | | | | | Insulation class: | I | | | | | Marks: | |  |  |  |  | Power supply: | | | | | 230 V, 50 Hz | | | | | | 24 V, 50 Hz |
| Protection class: | IP42 (IP67) |  |  |  | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Admissible ambient temperature: | t_a 30 °C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Insulation class: | I | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Marks: | |  |  |  |  | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Power supply: | | | | | 230 V, 50 Hz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | 24 V, 50 Hz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | <p>Rambo N</p> | <table border="1"> <tr> <td>Protection class:</td> <td>IP67</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="5">t_a 40 °C</td> </tr> <tr> <td>Insulation class:</td> <td colspan="5">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td colspan="4">II 3GD; EEx nA II T5</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="5">230 V, 50 Hz</td> </tr> </table> | Protection class: | IP67 |  |  |  | | Admissible ambient temperature: | t_a 40 °C | | | | | Insulation class: | I | | | | | Marks: |  | II 3GD; EEx nA II T5 | | | | |  |  |  |  | | Power supply: | 230 V, 50 Hz | | | | |
| Protection class: | IP67 |  |  |  | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Admissible ambient temperature: | t_a 40 °C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Insulation class: | I | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Marks: |  | II 3GD; EEx nA II T5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| |  |  |  |  | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Power supply: | 230 V, 50 Hz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---------------------------------|----------------------------|--|--|--|-------------------|---|--|--|--|--------|---|---|---|---|--|---|---|---|---|---------------|--------------|--|--|--|
|  | <p>Aqua N</p> | <table border="1"> <tr> <td>Protection class:</td> <td>IP67</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="4">t_a 40 °C</td> </tr> <tr> <td>Insulation class:</td> <td colspan="4">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td colspan="3">II 3GD; EEx nA II T5</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="4">230 V, 50 Hz</td> </tr> </table> | Protection class: | IP67 |  |  | | Admissible ambient temperature: | t_a 40 °C | | | | Insulation class: | I | | | | Marks: |  | II 3GD; EEx nA II T5 | | | |  |  |  |  | Power supply: | 230 V, 50 Hz | | | |
| Protection class: | IP67 |  |  | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Admissible ambient temperature: | t_a 40 °C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Insulation class: | I | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Marks: |  | II 3GD; EEx nA II T5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| |  |  |  |  | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Power supply: | 230 V, 50 Hz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | <p>Rambo Ex</p> | <table border="1"> <tr> <td>Protection class:</td> <td>IP67</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="4">t_a 40 °C</td> </tr> <tr> <td>Insulation class:</td> <td colspan="4">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td colspan="3">II 2GD; EEx edm IIC T5</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="4">230 V, 50 Hz</td> </tr> </table> | Protection class: | IP67 |  |  | | Admissible ambient temperature: | t_a 40 °C | | | | Insulation class: | I | | | | Marks: |  | II 2GD; EEx edm IIC T5 | | | |  |  |  |  | Power supply: | 230 V, 50 Hz | | | |
| Protection class: | IP67 |  |  | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Admissible ambient temperature: | t_a 40 °C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Insulation class: | I | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Marks: |  | II 2GD; EEx edm IIC T5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| |  |  |  |  | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Power supply: | 230 V, 50 Hz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | <p>Aqua Ex</p> | <table border="1"> <tr> <td>Protection class:</td> <td>IP67</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="4">t_a 40 °C</td> </tr> <tr> <td>Insulation class:</td> <td colspan="4">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td colspan="3">II 2GD; EEx edm IIC T5</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="4">230 V, 50 Hz</td> </tr> </table> | Protection class: | IP67 |  |  | | Admissible ambient temperature: | t_a 40 °C | | | | Insulation class: | I | | | | Marks: |  | II 2GD; EEx edm IIC T5 | | | |  |  |  |  | Power supply: | 230 V, 50 Hz | | | |
| Protection class: | IP67 |  |  | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Admissible ambient temperature: | t_a 40 °C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Insulation class: | I | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Marks: |  | II 2GD; EEx edm IIC T5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| |  |  |  |  | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Power supply: | 230 V, 50 Hz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | <p>Pitbul Ex</p> | <table border="1"> <tr> <td>Protection class:</td> <td>IP65</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="4">t_a 40 °C</td> </tr> <tr> <td>Insulation class:</td> <td colspan="4">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td colspan="3">II 2GD; EEx edm IIC T5</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Power supply:</td> <td colspan="4">230 V, 50 Hz</td> </tr> </table> | Protection class: | IP65 |  |  |  | Admissible ambient temperature: | t_a 40 °C | | | | Insulation class: | I | | | | Marks: |  | II 2GD; EEx edm IIC T5 | | | |  |  |  | | Power supply: | 230 V, 50 Hz | | | |
| Protection class: | IP65 |  |  |  | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Admissible ambient temperature: | t_a 40 °C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Insulation class: | I | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Marks: |  | II 2GD; EEx edm IIC T5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| |  |  |  | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Power supply: | 230 V, 50 Hz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  | <p>Boxer</p> | <table border="1"> <tr> <td>Protection class:</td> <td>IP54</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Admissible ambient temperature:</td> <td colspan="4">t_a 25 °C</td> </tr> <tr> <td>Insulation class:</td> <td colspan="4">I</td> </tr> <tr> <td>Marks:</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td colspan="4">IK 10 acc. CSN EN 50102</td> </tr> <tr> <td>Power supply:</td> <td colspan="4">230 V, 50 Hz</td> </tr> </table> | Protection class: | IP54 |  |  | | Admissible ambient temperature: | t_a 25 °C | | | | Insulation class: | I | | | | Marks: |  |  |  |  | | IK 10 acc. CSN EN 50102 | | | | Power supply: | 230 V, 50 Hz | | | |
| Protection class: | IP54 |  |  | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Admissible ambient temperature: | t_a 25 °C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Insulation class: | I | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Marks: |  |  |  |  | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | IK 10 acc. CSN EN 50102 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Power supply: | 230 V, 50 Hz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |